Γ	ጃ በ		ו	0	Ξ	A		]
4				LAYOUT SHOWN AS	EXAMPLE			4
	Keying Shown as example							
	CHARACTERISTICS Connector din	nension						
	-Standard : Based on MIL-DTL-38999 Series III Dim Dim	Nominal						
	-Shell Material     : Aluminium       -Shell Plating     : Nickel       -Insulator     : Thermoplastic       -Contacts     : Copper Alloy	35 Max 31.5 Max M31x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)					
N	-Seals & Grommet : Silicon Elastomer			Cour		& Control List Listed	]	2
	-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories			PN: 8D121		. Listeu		
	-Temperature Range -65°C to +200°C		A 23-09-2016	First Release				-
	-Salt Spray : 48 hours	-	ISS DATE	Latest modification - by			MOD N°	
			Designed By:	Date:	CUS	STOMER DRAWING		-
			TITLEAluminium Inline plug 8D series			) series		
_	BASIC SERIES:     8D     1     -     21     F     16     B       SHELL TYPE     : In line Receptacle     I     I     I     I     I		SCALE .	General linear Tolerances:	N	NPRDS / PROJECT 859		1
	SHELL TYPE     : In line Receptacie       CONTACT TYPE     : Standard Crimp Contact       SHELL SIZE     : 21   CONTACT TYPE : SOCKET(500 Matings)		SOURIAU         This document is the prope           SOURIAU         SOURIAU           it must not be reproduced communicated without permittion					
						ermission		
	PLATING : F = Nickel	CONTACT LAYOUT : 21-16	FORMAT A3		J DRG N° 16BB-C		SHEET 1/2	
1								

	<b></b>	െ	<del>ات</del>	m		0	
		Contact Layout					
4	ж.	$ \begin{array}{c} & & & & \\ & & & & \\ & & & & \\ & & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & \\ & & & $					
	Contact position ID         Locat           A         +.118 (3.00)           B         +.271 (6.88)           C         +.341 (8.66)           D         +.308 (7.82)           E         +.182 (4.62)           F         +.000 (0.00)           G        182 (4.62)	Y-axis         position ID         X-axis         Y-axis           +.322 (8.18)         J        341 (8.66)         +.036 (0.91)           +.211 (5.36)         K        271 (6.88)         +.211 (5.36)           +.036 (0.91)         L        118 (3.00)         +.322 (8.18)          150 (3.81)         M         +.000 (0.00)         +.175 (4.45)          290 (7.37)         N         +.154 (3.91)         +.062 (1.57)          343 (8.71)         P         +.094 (2.39)        122 (3.10)					
ω	H    308 (7.82)       Shell     Arrangement no.     Nun cor       21     -16						
	-					SOURIAU shall not be liab due to a use of the Pro the Specifications issued by (professional recor	oducts w / either c
N						PN: 8[	Count FR D121
					A 23-09-20 ISS DATE Designed By:	116 First Release Latest modification - by Date:	
					TITLE SCALE NA	Genera 	miniur al linear ances:
					SOURIA		IAU.(
		1	I	7	A3	8D:	121F
	Н	G	F	E	D	C	

