




Oct.1.2018 Copyright 2018 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case that the application demands a high level of reliability, such as automotive,
 please contact a company representative for further information.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE		STORAGE TEMPERATURE RANGE	
	POWER		CHARACTERISTIC IMPEDANCE	
SPECIFICATIONS				
ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
				
REMARK		APPROVED	HO.MIWA	06.10.27
		CHECKED	HO.MIWA	06.10.27
		DESIGNED	SJ.SHIMIZU	06.10.27
		DRAWN	SJ.SHIMIZU	06.10.27
Unless otherwise specified, refer to JIS C 5402.				
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-043523-01	
	SPECIFICATION SHEET	PART NO.	TM-8-DC1	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL222-2261-9-00	 1/1