

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C
	OPERATING&STORAGE HUMIDTY RANGE	85%MAX	APPLICABLE CABLE	CABLE DIAMETER : φ9.1~10.1
	CURRENT		VOLTAGE	

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
2	DIS-E-003060	TM. ONO	KN. ICHIKAWA	09. 12. 14

REMARK THIS PRODUCT SHALL BE MATED WITH DH3*B-51S, IT APPLIES TO DH3*B-51S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402.	APPROVED	AO. SUZUKI	09. 04. 28
	CHECKED	KN. ICHIKAWA	09. 04. 28
	DESIGNED	MO. SHIMOYAMA	09. 04. 28
	DRAWN	MO. SHIMOYAMA	09. 04. 28

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-126870-00
----------------------------------------------------------------	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DH-51-CT1B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0044-7-00	1/1