т (Органија) - Порија - Пори	m		0	œ		
			LAYOUT SHOWN	AS EXAMPLE		
Keying Shown as exam	ple					
	Connector dimension					
-Standard : Based on MIL-DTL-38999 Series III D	im Nominal					
-Shell Material : Aluminium	ØS 35.7 Max Z 31 Max HREAD M25x1-6g	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with				
-Insulator : Thermoplastic -Contacts : Copper Alloy			the Specifications issued by eith (professional recomme			
-Seals & Grommet : Silicon Elastomer		L			on & Control List	
-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles				FR N	lot Listed	
-Delivered with Souriau contacts and Accessories			PN: 8D5:	17F06SE		
-Temperature Range : -65°C to +200°C		A 14-10-201	16 First Release			
-Salt Spray : 48 hours -Mass : 39.5 g ± 10%		ISS DATE	Latest modification - by			MOD N°
		Designed By:	Date:	(USTOMER DRAWING	
		TITLE	TITLE Aluminium Plug 8D series			
BASIC SERIES: 8D 5 - 17 F 06 S E		SCALE	General line Tolerances		NPRDS / PROJECT	
SHELL TYPE : Plug with RFI Shielding		NA			859 This document is the pro	operty of
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 17	ORIENTATION : E CONTACT TYPE : SOCKET(500 Matings)	SOURIAU WWW.SOURIAU.COM it must not be reproduced or communicated without permissi			iced or	
PLATING : F = Nickel	CONTACT TYPE : SOCKET(SOU Matings)	FORMAT			communicated without p	SHEET
		A3		AU DRG N° 7F06SE-C		1/2

	т		Q	T T	m		0	
		Contact	Layout					
4		-x (D = F	$ \begin{array}{c} + Y \\ A \\ \oplus \\ O \\ \end{array} \\ \end{array} $					
		Contact position ID X-avis	-Y inte mment 17-6) Location					
ω	Shell Arrange size noo	(mm) A +121 (3) B +241 (6) C +.000 (0) D 241 (6) E 121 (3) F +.000 (0) ement Number of contacts contacts contacts	(mm) 07) + 209 (5.31) 12) + 000 (0.00) 00) - 241 (6.12) 12) + 000 (0.00) 07) + 209 (5.31) 00) + 000 (0.00) e Service Contact Supersu					
							due to a	hall not be liable for ar use of the Products w ions issued by either c
22							(prof	fessional recommenda Count FR
						A ISS Designed	14-10-2016 First Release DATE Latest modific d By: Date Datest Modific	PN: 8D517
_								General linear Tolerances:
_								W.SOURIAU.C
						FORM/ A3		SOURIAU 8D517F
	Н		G	F	E	D	C	

