

Specification Sheet

Part Number: 170-03063



Braided Sleeving, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver 100 ft/reel

Article Number

170-03063

Type

BSHTTST34SR

Color

Silver (SR)

Features & Benefits

- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
- Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
- Cuts with ordinary scissors for fast, easy application.

Product Description

A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

Short Description

Braided Sleeving, Aluminum Laminated Fiberglass, .75" Dia, AL/GF, Silver 100 ft/reel

Global Part Name

BSHTTST34SR-AL/GF-ML

Length L (Imperial)	100.0
Length L (Metric)	30.48
Bundle Diameter Min (Imperial)	0.1
Bundle Diameter Min (Metric)	2.54
Bundle Diameter Max (Imperial)	0.687
Bundle Diameter Max (Metric)	17.5
Diameter D (imperial)	0.75
Diameter D (metric)	19.1
Nominal Diameter (Imperial)	3/4
Nominal Diameter (Metric)	19.1
Wall Thickness WT (Imperial)	0.025
Wall Thickness WT (Metric)	0.64
Material	Aluminum (AL) Glass Fiber (GF)
Material Shortcut	AL GF
Flammability	Non-Flammable

Halogen free Yes

Operating Temperature (Metric) -76°F to +491°F (-60°C to +255°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Package Quantity(Imperial) 100

Package Quantity (Metric) 30.48

Customs Number 7019901000

Weight (Metric) 1.57

Weight (Imperial) 3.45