	T O	т <u>п</u>	D	C	B	A		_
4 ω	R 22.6 Max () () () () () () () () () () () () () (	S T T T T T T T T T T T T T T T T T T T			WN AS EXAMPLE			4
	CHARACTERISTICS -Standard : Based on MIL-DTL-38999 Series III	Keying Shown as example       Connector dimension       Dim     Nominal						
N	-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum-Durability: 500 Mating cycles	A     34.9±0.3       B     19.07+0.1/-0.15       R     32.5Max       S     31.8±0.4       W     2.2+0.9/-0.1       VV THREAD     M15x1-6g		the Specifications issued by	ducts which does not comp either of the Parties or by nmendation, technical noti Country Jurisdict	bly with a third party		2
	-Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours			2016 First Release	711W98SA			-
	-Mass : 20.65 g ± 10%		ISS DAT Designed By:	E Latest modification - by Date:		CUSTOMER DRAWING	MOD N°	
		TITLE Aluminium Receptacle 8D series						
<u> </u>	BASIC SERIES:8D7-11W98SHELL TYPE : Jam nut Receptacle	S A	SCALE NA	Genera Tolera ±	ances:	NPRDS / PROJECT 859		1
	CONTACT TYPE : Standard Crimp Contact   SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings)			SOURIAU     This document is the property of SOURIAU       SOURIAU     SOURIAU       it must not be reproduced or communicated without permission			d or	
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 11-98	FORMAT A3		RIAU DRG N° 11W98SA-C		SHEET 1/2	
L	H G	FEE	D	C	B	A		

ſ	Т	G	П	ш	D	0	Φ	A	
4	-X	Contact Layout $\downarrow \qquad \qquad$		Panel cutout JAM NUT RECEPTACLE (TYPE 7)					
	Shell Arrangement Numb size no. cont 11 -98 6	(mm)     (mm)       A     +.000 (0.00)     +.130 (3.30)       B     +.130 (3.30)     +.000 (0.00)       C     +.065 (1.65)    113 (2.87)       D    065 (1.65)    113 (2.87)       E    130 (3.30)     +.000 (0.00)       F     +.000 (0.00)     +.000 (0.00)				Dim     Nominal       B     19.59+0/-0.			
ω						ØC 20.96+0.25,			3
2						the Specifications issued by	ducts which does not con either of the Parties or by nmendation, technical no Country Jurisdic	nply with y a third party tice.) ction & Control List	
					A 01-10-201 ISS DATE	PN: 8D	<sup>FR</sup> 711W98SA	Not Listed MOD	2
					Designed By: TITLE	Date:	ninium Receptacle	CUSTOMER DRAWING	
<b>_</b>					SCALE NA SOURIAU		ances: 	NPRDS / PROJECT <b>859</b> This document is the property of SOURIAU it must not be reproduced or communicated without permission	1
	Н	G	F	E	FORMAT A3		RIAU DRG N° 11W98SA-C B	SHEE 2/2 A	
						-	—		