т © "	m		0	8		
Z M Lineard M M						
			LAYOUT SHOWN AS EXA	AMPLE		
Keying S	Shown as example					
CHARACTERISTICS	Connector dimension					
Standard : Based on MIL-DTL-38999 Series III	Dim Nominal ØS 25 Max					
-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy	Z31 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any due to a use of the Products whic the Specifications issued by either of t (professional recommendation)	ch does not comply with he Parties or by a third party		
-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum			Country FR	Jurisdiction & Control List Not Listed		
-Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories			PN: 8D511W			
-Temperature Range - 65°C to +175°C		A 18-10-2016	First Release			
-Salt Spray : 500 hours -Mass : 14.87 g ± 10%		ISS DATE	Latest modification - by		MOD N°	
-Wass . 14.07 g ± 10/0		Designed By:	Date:	CUSTOMER DRAWING		
		TITLE Aluminium Plug 8D series		um Plug 8D series		
BASIC SERIES: 8D 5 - 11 W 99 A SHELL TYPE : Plug with RFI Shielding - 11 W 99 A	A	SCALE	General linear Tolerances:	NPRDS / PROJECT 859		
CONTACT TYPE : Standard Crimp Contact	ORIENTATION : A			This document is the propert SOURIAU	ty of	
SHELL SIZE : 11	CONTACT TYPE : PIN(500 Matings)			SOURIAU WWW.SOURIAU.COM it must not be reproduced or communicated without permission		
PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 11-99	FORMAT	SOURIAU		SHEET	
		A3	8D511W9		1/2	

_	т	۵	н п	т	D	0	
		Contact Layout					
4	-×	$ \begin{array}{c} & \bullet & \bullet \\ & \bullet & \bullet$					
	Cont positi ID A B C D E F G Shell Arrangement Numt size no. cont	X-axis (mm) Y-axis (mm) +.065 (1.65) +.113 (2.87) +.130 (3.30) +.000 (0.00) +.065 (1.65) 113 (2.87) 065 (1.65) 113 (2.87) 065 (1.65) +.113 (2.87) 065 (1.65) +.113 (2.87) 065 (1.65) +.113 (2.87) 065 (1.65) +.113 (2.87) 065 (1.65) +.113 (2.87) 006 (0.00) +.000 (0.00) 065 (1.65) extra (2.87) 006 (0.00) +.000 (0.00)	1				
cى	size no. cont 11 -99 7						
	-					SOURIAU shall not be liable due to a use of the Prod the Specifications issued by e	ducts wh
N						(professional recom	Countr FR
						PN: 8D5	511V
					ISS DATE Designed By: TITLE	Latest modification - by Date:	lumin
-					SCALE NA SOURIAI	General Tolerar ±	nces: -
					FORMAT A3	SOUR 8D51	RIAU
L	Н	G	F	E	D	С	

