т р С	m		0	₩ >	
			LAYOUT SHOWN AS EXAN	APLE	
CHARACTERISTICS	wn as example				
-Standard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal				
-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8μm minimum	ØS25 MaxZ31 MaxVV THREADM15x1-6g		SOURIAU shall not be liable for any no due to a use of the Products which the Specifications issued by either of th (professional recommendation Country FR	does not comply with e Parties or by a third party	
-Durability: 500 Mating cycles-Delivered with Souriau contacts and Accessories			PN: 8D511W9	99AC	
-Temperature Range : -65°C to +175°C		A 18-10-2016	First Release		
-Salt Spray : 500 hours -Mass : 14.87 g ± 10%		ISS DATE	Latest modification - by	N	MOD N°
		Designed By:	Date:	CUSTOMER DRAWING	
		TITLE	TITLEAluminium Plug 8D series		
BASIC SERIES:     8D     5     -     11     W     99     A     C       SHELL TYPE     : Plug with RFI Shielding     -     11     W     99     A     C		SCALE	General linear Tolerances:	NPRDS / PROJECT <b>859</b>	
CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11	ORIENTATION : C CONTACT TYPE : PIN(500 Matings)	SOURIAU			r
PLATING : W = Olive drab Cadmium	CONTACT TYPE : PIN(500 Matings)	FORMAT	SOURIAU D	communicated without permission	SHEET
		A3	8D511W99		1/2
					,

_	т	۵	г П	т		0	
		Contact Layout					
4	-8	$ \begin{array}{c}                                     $					
		X-axis         Y-axis           (mm)         (mm)           A         +.065 (1.65)         +.113 (2.87)           B         +.130 (3.30)         +.000 (0.00)           C         +.065 (1.65)        113 (2.87)           D        065 (1.65)        113 (2.87)           E        130 (3.30)         +.000 (0.00)           F        065 (1.65)         +.113 (2.87)	]				
ω		itacts contacts rating location 7 20 I All MS20050-99					
	-					SOURIAU shall not be liab due to a use of the Pro	oducts wh
N						the Specifications issued by (professional recor	y either of mmendat Countr FR
						PN: 8D	)511V
					A 18-10-20 ISS DATE Designed By:	016 First Release Latest modification - by Date:	
					SCALE		Alumin
<u> </u>					NA		rances: ±
					SOURIA		
					FORMAT A3	8D5	RIAU 511W
	Н	G	F	E	D	C	

